



SAF Series

Automatic self-cleaning filters,
perfect for filtering poor quality
water and ideal for numerous
applications



flowrates

**up to 400 m³/h
(1,760 gpm)**

filtration degrees

800-10 micron

water for cleaning

**less than 1%
of the total flow**

minimum working
pressure

2 bar (30 psi)

features:

- Large filter area, reliable operating mechanism and simple construction make the SAF filters the ideal solution for filtration of poor water quality to very fine filtration
- Automatic self-cleaning according to pressure differential and/or time
- No interruption of downstream flow during self-cleaning
- Robust and reliable self-cleaning mechanism, even in marginal operating conditions
- Applications: municipal water supply systems, cooling water, wastewater treatment, industrial pre-filtration, membrane protection, irrigation systems etc.
- Industries: manufacturing, oil and gas, mining, water and wastewater treatment plant, turf and agriculture, etc.

How the SAF filters work

General

The Amiad SAF filters are sophisticated, yet easy-to-operate, automatic filters, with a self-cleaning mechanism driven by an electric motor.

The “SAF” filters support flow-rates of up to 400 m³/h (1,760 gpm), with various screens designed to cover a range of filtration degrees, from 800 to 10 micron, and are available in inlet/outlet diameters of 2” to 10”.

The Filtering Process

Raw water enters the filter inlet (1) through the coarse screen (2) which protects the cleaning mechanism from large debris. The water passes through the fine screen (3), trapping dirt particles which accumulate inside the filter. Clean water flows through the filter outlet (4).

The gradual dirt buildup on the inner screen surface causes a filter cake to develop, with a corresponding increase in the pressure differential across the screen. A pressure differential switch senses the increased pressure differential and when it reaches a pre-set value (typically 7.0 psi), the cleaning process begins.

The Self-Cleaning Process

Cleaning of the filter is carried out by the suction scanner (5) which spirals across the screen. The open exhaust valve creates a high velocity suction stream at the nozzles tip which “vacuums” the filter cake from the screen. During the self-cleaning process, which takes between 20 to 40 seconds, filtered water continues to flow downstream.

The Control System

Operation and monitoring is done by PLC (Programmable Logic Controller). The PLC allows maximum operation flexibility and provides a wide range of control options from an independent stand-alone unit up to full integration within the customer’s central control system.

Initiation of self-cleaning process:

1. Flushing by pressure differential – DP analog or digital signal
2. Flushing by time intervals
3. Continuous flushing – regardless of DP or time
4. Remote or local manual start


The PLC also provides:

- Flush cycle counter
- Cause of flushing statistics
- Faults and alarms, reaction and messages


“SAF” Models

Amiad’s “SAF” product-line consists of the following models:

- SAF 1500 for up to 80 m³/h (350 gpm)
- SAF 3000 for up to 150 m³/h (660 gpm)
- SAF 4500 for up to 250 m³/h (1,100 gpm)
- SAF 6000 for up to 400 m³/h (1,760 gpm)




SAF 1500



SAF 3000




SAF 4500










SAF 6000



Typical Installation Drawing



Head Loss Graphs
in clean water



Dim: mm (inch)

*Approx. length required for maintenance

Technical Specifications

Filter	SAF 1500	SAF 3000	SAF 4500	SAF 6000
--------	----------	----------	----------	----------

General Data				
Maximum flowrate*	80 m³/h (350 gpm)	150 m³/h (660 gpm)	250 m³/h (1,100 gpm)	400 m³/h (1,760 gpm)
Inlet/Outlet diameter	2" (50 mm) 3" (80 mm) 4" (100 mm)	3" (80 mm) 4" (100 mm) 6" (150 mm)	4" (100 mm) 6" (150 mm) 8" (200 mm)	6" (150 mm) 8" (200 mm) 10" (250 mm)
Standard filtration degrees	800, 500, 300, 200, 130, 100, 80, 50, 25, 10 micron			
Min. working pressure	2 bar (30 psi) For lower pressure please consult manufacturer			
Max. working pressure	10 bar (150 psi)		10 bar (150 psi) 16 bar (232 psi) upon request	
Max. working temperature	50°C (122°F)		60°C (140°F) 95°C (203°F) upon request	
Weight [empty]	86 kg (190 lb)	110 kg (242.5 lb)	160 kg (353 lb)	250 kg (551 lb)

* Consult Amiad for optimum flow depending on filtration degree and water quality.

Flushing Data				
Minimum flow for flushing (at 2 bar -30 psi)	6 m³/h (26 gpm)	11 m³/h (48 gpm)	15 m³/h (66 gpm)	25 m³/h (110 gpm)
Reject water volume per flush cycle (at 2 bar-30 psi)	25 liter (7 gallon)	64 liter (17 gallon)	83 liter (22 gallon)	280 liter (74 gallon)
Flushing cycle time	15 seconds	20 seconds		40 seconds
Exhaust valve	2" (50 mm)			
Flushing criteria	Differential pressure of 0.5 bar (7psi), time intervals and manual operation			

Screen Data				
Filter area	1,500 cm² (323 in²)	3,000 cm² (465 in²)	4,500 cm² (697 in²)	6,000 cm² (930 in²)
Screen types	Four-layer weavewire stainless steel 316L			
	Molded weavewire stainless steel 316L			

Control and Electricity		
Rated operation voltage	115 - 480 VAC, 1 or 3 PH, 50 or 60 Hz	
Electric motor	¼ HP	⅓ HP
Current consumption	0.6 Amp	0.8 Amp
Control voltage	24 VAC 12V or 24VAC, upon request	

Construction Materials*	
Filter housing	Epoxy-coated carbon steel 37-2
Filter lid	SMC polyester/epoxy-coated carbon steel 37-2
Cleaning mechanism	Stainless steel 316L, acetal
Exhaust valve	Epoxy-coated cast iron, natural rubber
Seals	Synthetic rubber, teflon
Control	Aluminum, brass, stainless steel, PVC, nylon

* Amiad offers a variety of construction materials. Consult us for specifications.

Headquarters

Amiad Water Systems Ltd. D.N. Galil Elyon 1, 1233500, Israel,
Tel: +972 4 690 9500, Fax: +972 4 814 1159,
E-mail: info@amiad.com

The Americas



Amiad USA Inc. Main Office and Manufacturing: 120-J Talbert Road, Mooresville, NC 28117,
Tel: +1 704 662 3133, Fax: +1 704 662 3155, Toll Free: +1 800 24 FILTER,
E-mail: infousa@amiad.com www.amiadusa.com

West Coast Sales Office and Warehouse:
1251 Maulhardt Ave, Oxnard, CA 93030
Tel: +1 805 988 3323, Fax: +1 805 988 3313, Toll Free: +1 800 969 4055

Brazil

Amiad Sistemas de Água Ltda., Rua Funchal, 411, Conj. 42, Vila Olimpia, São Paulo, CEP 04551-060
Tel: +55 11 31923824, E-mail: infobrasil@amiad.com

Amiad Oil & Gas, E-mail: amisur@adinet.com.uy

Mexico

Amiad México SA DE CV, AV. Jesus del Monte #39B – INT 601, Col. Jesus del Monte,
C.P. 52764, Huixquilucan, Estado de México, Tel/Fax: +52 55 636 28122, Mob: +52 1 55 4909 2202
E-mail: infomexico@amiad.com

Irrigation Office: infomexico-irr@amiad.com

Asia



India

Amiad Filtration India Pvt Limited, 305 Sai Commercial Building,
Govandi St Rd, Govandi Mumbai 400 088,
Tel: +91 22-67997813/14, Fax: +91 22-67997814, Email: info@amiadindia.com

China

Amiad China (Yixing Taixing Environtec Co., Ltd.) 70 Baihe Chang, Xingjie Yixing Jiangsu, 214204,
Tel: +86 510 87134000, Fax: +86 510 87134999, E-mail: marketing@taixing.cc

South-East Asia

Filtration & Control Systems Pte. Ltd., 22 Sin Ming Lane #07-71 Midview City, Singapore 573969,
Tel: +65 6 337 6698, Fax: +65 6 337 8180, E-mail: amiad@amiad.com.sg

Australia



Amiad Australia Pty Ltd. 138 Northcorp Boulevard, Broadmeadows, Victoria 3047,
Tel: +61 3 93585800, Fax: +61 3 93585888, E-mail: sales@amiad.com

Europe



Amiad Water Systems Europe SAS, Ilot No4 ZI La Boitardière, 37530 Chargé, France,
Tel: +33 (0) 2 47 23 01 10, Fax: +33 (0) 2 47 23 80 67, E-mail: industry-europe@amiad.com

Amiad Water Systems Europe SAS (Irrigation Division)
100 avenue de l'Anguillon, Z.I. des Iscles, 13160 Chateaurenard,
Tel: +33 (0) 4 32 60 10 01, Fax +33 (0) 4 32 60 60 85

Germany

Amiad Water Systems SAS Europe (German branch office)
Zweigniederlassung Deutschland Prinz-Regent-Str. 68 a 44795 Bochum,
Tel: +49 (0) 234 588082-0, Fax: +49 (0) 234 588082-10, E-mail: info@amiad.de

United Kingdom

Amiad Water Systems UK Limited, Unit 1 Heol Rhosyn, Dafen Business Park,
Dafen, Llanelli SA14 8QG,
Tel: +44 (0)1792 277290, Fax: +44 (0)1792 797707, E-mail: info-uk@amiad.com

