

AIRFLO AND WHISPERAIR BLOVERS

Whisper quiet performance



- Whisper quiet operation
- Hi-flow air movement
- Compact design
- Variable mounts

www.waterco.com

Compact Design

The compact design of Waterco's spa blowers enables installation in smaller areas and tight corners. The convenient position of the mounting base and air inlet/outlets reduces installation time and cost.

Thermal Cutout

Waterco spa blowers feature an important safety feature, an integral thermal cutout. This cutout stops the electric motor from becoming excessively warm. This cutout does not require manual resetting and will automatically restart the motor when it has sufficiently cooled.

Standard Model – Airflo, Whisperair, Whisperair S

The standard model of the blower draws air into the unit through the bottom cowl of the blower.

The airflo version has air inlet holes throughout the bottom cowl, while the Whisperair models draw all the required air in through gaps around the perimeter of the bottom cowl.

Air switch Models (Whisperair S and Whisperair S Elite)

The Whisperair S comes with an air switch controller and connecting tubing to provide remote activation / deactivation of the blower. The button for the air switch controller is designed to be installed in the shell of the spa and is connected to the blower via tubing.

Variable mounts

All Waterco Blower's have two identical 50mm diameter outlet ports. One of the ports is in the bottom cowl of the blower and the other is in the side of the blower. The stand can be attached to either of these ports and leaves the other free to connect to the spa via the piping. It is also possible to connect the pipe to the outlet port in the bottom cowl of the blower and seal off the other outlet port.



Technical Data

Product Description	Power (Watts)	Amps (A)	Max. Operating Pressure (kPa)	Max. Flow Rate (It /sec)	Max. Operating Noise (dBa)	Voltage (V)	Cycle (Hz)	Unit Weight (kg)	Electrical Protection Rating	Inlet / Outlet Ports (mm)
Airflo Spa Blower	900	4.0	17	72	91.6	220-240	50	5	IP23	50
Whisperair Spa Blower	900	4.0	17	72	91.0	220-240	50	5	IP23	50
Whisperair Spa Blower with Air Switch	900	4.0	17	72	91.0	220-240	50	5	IP23	50
Airflo Spa Blower	1200	5.8	27	72	94.6	220-240	50	5	IP23	50
Whisperair Spa Blower	1200	5.8	27	72	94.0	220-240	50	5	IP23	50
Whisperair Spa Blower with Air Switch	1200	5.8	27	72	94.0	220-240	50	5	IP23	50

Warranty

Waterco blowers are covered by a comprehensive 12 month warranty.

Note: Waterco 900/1200 watt blowers are designed for domestic use, only. They operate with a heat switch that will automatically cut out @ 900 watt / 125° & 1200 watt / 165°. Good ventilation is recommended to help maintain good air flow and temperature control.

 OFFICES - AUSTRALIA

 NSW - Sydney (Head Office

 Tel: +61 2 9898 8600

 QLD - Brisbane

 Tel: +61 7 3299 9900

 VIC/TAS - Melbourne

 Tel: +61 3 9764 1211

 WA - Perth

 Tel: +61 8 9273 1900

 SA/NT - Adelaide

 Tel: +61 8 8244 6000

 ACT Distribution

 Tel: +61 2 6280 6476

OFFICES - OVERSEAG Waterco (Europe) Limited Sittingbourne, Kent. UK Tel: +44 (0) 1795 521 733 Waterco (USA) Inc Augusta, Georgia, USA Tel: +1 706 793 7291 Waterco Canada Longueuil, Quebec, Canada Tel: +1 450 748 1421 Waterco (NZ) Limited Auckland, New Zealand Tel: +64 9 525 7570

Waterco (C) Limited Guangzhou, China Tel: +86 20 3222 2180 Waterco (Far East) Sdn Bhd Selangor, Malaysia Tel: +60 3 6145 6000 PT Waterco Indonesia Jakarta, Indonesia Tel: +62 21 4585 1481 Waterco Singapore Intl Pte Ltd Nehsons Building, Singapore Tel: +65 6344 2378 /aterco France AINT PRIEST, France el: +33 4 72 79 33 30 DISTRIBUTED BY: Chainaris Phuket Engineering Co., Ltd. 63/13 Moo.2, T.Vichit, A.Muang Phuket 83000 Tel: 076-513100-4 Fax: 076-513105 Line: @chainaris, @chainarisshop



In the interest of providing better quality and value we are constantly improving and updating our products. Consequently, pictures and information on our brochures may sometimes vary slightly from models available